

STATE WASTE DISCHARGE PERMIT Number ST-7316

STATE OF WASHINGTON
DEPARTMENT OF ECOLOGY
Northwest Regional Office
3190 – 160th Avenue SE
Bellevue, WA 98008-5452

In compliance with the provisions of the
State of Washington Water Pollution Control Law
Chapter 90.48 Revised Code of Washington, as amended,
and
the Federal Water Pollution Control Act
(The Clean Water Act)
Title 33 United States Code, Section 1251 et seq.,
authorizes

ARTISAN FINISHING SYSTEMS, INC.

14219 Smokey Point Boulevard #6

Marysville, WA 98271-8906

to discharge wastewater in accordance with the special and general conditions which follow.

Facility Address:

Artisan Finishing Systems, Inc.
14219 Smokey Point Boulevard #6
Marysville, WA 98271-8906

Discharge Location:

Latitude: 48° 07' 36" N
Longitude: 122° 10' 56" W

Publicly Owned Treatment Works (POTW) Receiving Discharge: City of Marysville

Industry Type:

Chromium Conversion Coating
and Painting

SIC Code:

3479
Categorical Significant Industrial User

Kevin C. Fitzpatrick
Water Quality Section Manager
Northwest Regional Office
Washington State Department of Ecology

TABLE OF CONTENTS

SUMMARY OF PERMIT REPORT SUBMITTALS.....	4
SPECIAL CONDITIONS	
S1. DISCHARGE LIMITATIONS.....	5
S2. MONITORING REQUIREMENTS.....	5
A. Wastewater Monitoring	
B. Sampling and Analytical Procedures	
C. Flow Measurement	
D. Laboratory Accreditation	
S3. REPORTING AND RECORDKEEPING REQUIREMENTS	7
A. Reporting	
B. Records Retention	
C. Recording of Results	
D. Additional Monitoring by the Permittee	
E. Noncompliance Notification	
F. Dangerous Waste Discharge Notification	
G. Spill Notification	
S4. OPERATIONS AND MAINTENANCE.....	9
A. Operations and Maintenance Manual	
B. Bypass Procedures	
C. Best Management Practices\Pollution Prevention Program	
S5. PROHIBITED DISCHARGES.....	12
A. General Prohibitions	
B. Specific Prohibitions	
C. Prohibited Unless Approved	
S6. DILUTION PROHIBITED.....	13
S7. SOLID WASTE DISPOSAL.....	13
A. Solid Waste Handling	
B. Leachate	
C. Solid Waste Control Plan	
S8. NON-ROUTINE AND UNANTICIPATED DISCHARGES.....	14
S9. SPILL PLAN	14
S10. SLUG DISCHARGE CONTROL PLAN.....	15
S11. TOXIC ORGANIC MANAGEMENT PLAN.....	16
S12. STORMWATER POLLUTION CONTROL	16

GENERAL CONDITIONS

G1.	SIGNATORY REQUIREMENTS.....	18
G2.	RIGHT OF ENTRY	18
G3.	PERMIT ACTIONS.....	19
G4.	REPORTING A CAUSE FOR MODIFICATION	19
G5.	PLAN REVIEW REQUIRED	19
G6.	COMPLIANCE WITH OTHER LAWS AND STATUTES.....	19
G7.	DUTY TO REAPPLY	20
G8.	PERMIT TRANSFER	20
G9.	REDUCED PRODUCTION FOR COMPLIANCE	20
G10.	REMOVED SUBSTANCES	20
G11.	PAYMENT OF FEES.....	20
G12.	PENALTIES FOR VIOLATING PERMIT CONDITIONS	20

SUMMARY OF PERMIT REPORT SUBMITTALS

Refer to the Special and General Conditions of this permit for additional submittal requirements.

Permit Section	Submittal	Frequency	First Submittal Date
S3.A.	Discharge Monitoring Report with TTO Certification Statement	Monthly	August 15, 2004
S4.A.	Operation and Maintenance Manual Update	1/permit cycle	Within thirty days of adoption of update
S7.	Solid Waste Control Plan Update	As necessary	Within thirty days of adoption of update
S9.	Spill Plan Update	As necessary	Within thirty days of adoption of update
S10.	Slug Discharge Control Update	As necessary	Within thirty days of adoption of update
S11.	Toxic Organic Management Plan Update	1/permit cycle	Within thirty days of adoption of update
S12.	Stormwater Pollution Prevention Plan Update	1/permit cycle	Within thirty days of adoption of update
G7.	Application for permit renewal	1/permit cycle	December 30, 2008

SPECIAL CONDITIONS

S1. DISCHARGE LIMITATIONS

All discharges and activities authorized by this permit shall be consistent with the terms and conditions of this permit. The discharge of any of the following pollutants or flows more frequently than, or at a concentration in excess of, that authorized by this permit shall constitute a violation of the terms and conditions of this permit.

Beginning on the effective date and lasting through the expiration date of this permit, the Permittee is authorized to discharge wastewater to the City of Marysville sanitary sewer system subject to the following limitations:

EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS				
	EFFLUENT LIMITATIONS		MONITORING REQUIREMENTS	
Pollutant Parameter	Maximum Daily ^b	Average Monthly ^a	Sampling Frequency	Sample Type
Flow (process), gpd	5900	N/A	Daily	Metered
Cyanide(T), mg/L ^d	1.20	0.65	Once each six months	Grab ^e
Copper(T), mg/L ^c	0.5	0.5	Once each six months	Composite ^f
Nickel(T),mg/L ^c	1.48	1.48	Once each six months	Composite ^f
Chromium(T), mg/L ^c	1.47	1.47	Monthly	Composite ^f
Zinc(T), mg/L ^c	1.67	1.48	Once each six months	Composite ^f
Lead(T), mg/L ^c	0.52	0.43	Once each six months	Composite ^f
Cadmium(T), mg/L ^c	0.11	0.07	Once each six months	Composite ^f
Silver(T), mg/L ^c	0.43	0.24	Once each six months	Composite ^f
TTO, mg/L ^g	2.13	N/A	N/A	Grab
pH, std units	Not outside the range of 6.0 to 9.0		Daily	Grab
BOD ₅ , mg/L	300	N/A	N/A	N/A
TSS, mg/L	350	N/A	N/A	N/A

^a The average monthly effluent limitation is defined as the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month.

^b The maximum daily effluent limitation is defined as the highest allowable daily discharge. The daily discharge means the discharge of a pollutant measured during a calendar day. For pollutants with limitations expressed in units of mass, the daily discharge is calculated as the total mass of the pollutant discharged over the day. For other units of measurement, the daily discharge is the average measurement of the pollutant over the day.

^c A “(T)” following the name of a metal indicates total as opposed to dissolved.

- ^d A “(T)” following cyanide indicates total cyanide as opposed to cyanide amenable to chlorination.
- ^e The Permittee shall properly preserve the cyanide sample with ascorbic acid and sodium hydroxide to a pH of greater than 12.0 (See Handling and Preservation under EPA Method 335.2)
- ^f Daily composite samples shall consist of a minimum of four time proportional grab samples collected throughout the operating day from a well-mixed effluent chamber. In those six-month periods during which treatment of the concentrated chromium rinsewater is performed, the metals sample must be collected on the day during which the treated concentrated rinsewater is being discharged.
- ^g Organic chemicals comprising TTO’s are listed in 40 CFR Part 433.11(e). The term TTO shall mean the summation of all quantifiable values greater than 0.01 mg/L for the listed compounds. **The Permittee shall submit a signed Certification Statement with each monthly report in lieu of performing TTO sampling and analysis. The text of the Certification Statement shall read as follows: “ Based on my inquiry of the person or persons directly responsible for managing compliance with the permit limitation (or pretreatment standard) for total toxic organics (TTO), I certify to the best of my knowledge and belief, no dumping of concentrated organics into the wastewaters has occurred since filing of the last discharge monitoring report. I further certify that this facility is implementing the toxic organic management program submitted to the control authority.”** The requirement for submittal of a Toxic Organic Management Plan appears in Part S11. of this permit.

S2. MONITORING REQUIREMENTS

A. Wastewater Monitoring

The Permittee shall monitor the wastewater according to the schedule set forth in Special Condition S1 above.

B. Sampling and Analytical Procedures

Samples and measurements taken to meet the requirements of this permit shall be representative of the volume and nature of the monitored parameters, including representative sampling of any unusual discharge or discharge condition, including bypasses, upsets, and maintenance-related conditions affecting effluent quality.

Sampling and analytical methods used to meet the water and wastewater monitoring requirements specified in this permit shall conform to the latest revision of the *Guidelines Establishing Test Procedures for the Analysis of Pollutants* contained in 40 CFR Part 136 or to the latest revision of *Standard Methods for the Examination of Water and Wastewater* (APHA), unless otherwise specified in this permit or approved in writing by the Department of Ecology (Department).

C. Flow Measurement

Appropriate flow measurement devices and methods consistent with accepted scientific practices shall be selected and used to ensure the accuracy and reliability of measurements of the quantity of monitored flows. The devices shall be installed, calibrated, and maintained to ensure that the accuracy of the measurements are consistent with the accepted industry standard for that type of device. Frequency of calibration shall be in conformance with manufacturer's recommendations and at a minimum frequency of at least one (1) calibration per year. Calibration records shall be maintained for at least three (3) years.

D. Laboratory Accreditation

All monitoring data required by the Department shall be prepared by a laboratory registered or accredited under the provisions of, *Accreditation of Environmental Laboratories*, Chapter 173-50 WAC. Flow, temperature, settleable solids, pH, and internal process control parameters are exempt from this requirement.

S3. REPORTING AND RECORDKEEPING REQUIREMENTS

The Permittee shall monitor and report in accordance with the following conditions. The falsification of information submitted to the Department shall constitute a violation of the terms and conditions of this permit.

A. Reporting

The first monitoring period begins on the effective date of the permit. Monitoring results shall be submitted monthly. Monitoring results obtained during the previous month shall be reported on the monthly forms as provided, or otherwise approved, by the Department, and be received no later than the 15th day of the month following the completed reporting period, unless otherwise specified in this permit. One report form shall be completed for each month. The report shall be sent to the Department of Ecology, Northwest Regional Office, 3190 - 160th Avenue SE, Bellevue, Washington, 98008-5452. The Permittee is also required to submit copies of discharge monitoring reports to the City of Marysville, 80 Columbia Avenue, Marysville, WA 98270, on the same monthly schedule set forth above. The first report is due August 15, 2004

Discharge Monitoring Report forms must be submitted quarterly whether or not the facility was discharging. If there was no discharge, or the facility was not operating during a given monitoring period, the Permittee is required to submit the form as required with the words "no discharge" entered in place of the monitoring results.

The Permittee shall submit a signed Certification Statement with each monthly report in lieu of performing TTO sampling and analysis. The text of the Certification Statement shall read as follows:

“Based on my inquiry of the person or persons directly responsible for managing compliance with the permit limitation (or pretreatment standard) for total toxic organics (TTO), I certify to the best of my knowledge and belief, no dumping of concentrated organics into the wastewaters has occurred since filing of the last discharge monitoring report. I further certify that this facility is implementing the toxic organic management program submitted to the control authority.”

Signature of Authorized Representative: _____

Date: _____

B. Records Retention

The Permittee shall retain records of all monitoring information for a minimum of three (3) years. Such information shall include all calibration and maintenance records and all original recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit. This period of retention shall be extended during the course of any unresolved litigation regarding the discharge of pollutants by the Permittee or when requested by the Director.

C. Recording of Results

For each measurement or sample taken, the Permittee shall record the following information: (1) the date, exact place, method, and time of sampling; (2) the individual who performed the sampling or measurement; (3) the dates the analyses were performed; (4) who performed the analyses; (5) the analytical techniques or methods used; and (6) the results of all analyses.

D. Additional Monitoring by the Permittee

If the Permittee monitors any pollutant more frequently than required by this permit using test procedures specified by Condition S2. of this permit, then the results of this monitoring shall be included in calculation and reporting of the data submitted in the Permittee's self-monitoring reports.

E. Noncompliance Notification

In the event the Permittee is unable to comply with any of the permit terms and conditions due to any cause, the Permittee shall:

1. Immediately take action to stop, contain, and cleanup unauthorized discharges or otherwise stop the violation, and correct the problem;
2. Repeat sampling and analysis of any violation and submit the results to the Department within thirty (30) days after becoming aware of the violation;
3. Immediately notify the Department and the local sewage treatment plant manager of the failure to comply; and

4. Submit a detailed written report to the Department within thirty (30) days (five [5] days for upsets and bypasses), unless requested earlier by the Department. The report should describe the nature of the violation, corrective action taken and/or planned, steps to be taken to prevent a recurrence, results of the resampling, and any other pertinent information.

Compliance with these requirements does not relieve the Permittee from responsibility to maintain continuous compliance with the terms and conditions of this permit or the resulting liability for failure to comply.

F. Dangerous Waste Discharge Notification

The Permittee shall notify the POTW and the Department in writing of the intent to discharge into the POTW any substance designated as a dangerous waste in accordance with the provisions of WAC 173-303-070. This notification shall be made at least ninety (90) days prior to the date that discharge is proposed to be initiated.

G. Spill Notification

The Permittee shall notify the POTW immediately (as soon as discovered) of all discharges that could cause problems to the POTW, such as process spills and unauthorized discharges (including slug discharges).

S4. OPERATIONS AND MAINTENANCE

The Permittee shall at all times be responsible for the proper operation and maintenance of any facilities or systems of control installed to achieve compliance with the terms and conditions of the permit.

A. Operations and Maintenance Manual

A current Operations and Maintenance (O&M) Manual shall be maintained by the Permittee in accordance with WAC 173-240-150. The O&M Manual shall be reviewed by the Permittee at least annually. All manual changes or updates shall be submitted to the Department whenever they are incorporated into the manual. The approved Operation and Maintenance Manual shall be kept available at the permitted facility.

The Operation and Maintenance Manual shall contain the treatment plant process control monitoring schedule. All operators shall follow the instructions and procedures of this manual.

The manual shall include:

1. Emergency procedures for plant shutdown and cleanup in event of wastewater system upset or failure; and
2. Plant maintenance procedures.

B. Bypass Procedures

The Permittee shall immediately notify the Department and the receiving POTW of any spill, overflow, or bypass from any portion of the collection or treatment system.

The bypass of wastes from any portion of the treatment system is prohibited unless one of the following conditions (1, 2, or 3) applies:

1. Unavoidable Bypass—Bypass is unavoidable to prevent loss of life, personal injury, or severe property damage. “Severe property damage” means substantial physical damage to property, damage to the treatment facilities which would cause them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass.

If the resulting bypass from any portion of the treatment system results in noncompliance with this permit, the Permittee shall notify the Department and the receiving POTW in accordance with condition S3.E “Noncompliance Notification.”

2. Anticipated Bypass that has the Potential to Violate Permit Limits or Conditions—Bypass is authorized by an administrative order issued by the Department. The Permittee shall notify the Department and the POTW at least thirty (30) days before the planned date of bypass. The notice shall contain a description of the bypass and its cause; the duration of the bypass, including exact dates and times; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the bypass. The Department will consider the following prior to issuing an administrative order:
 - a. If the bypass is necessary to perform construction or maintenance-related activities essential to meet the requirements of the permit.
 - b. If there are feasible alternatives to bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, stopping production, maintenance during normal periods of equipment down time, or transport of untreated wastes to another treatment facility.
 - c. If the bypass is planned and scheduled to minimize adverse effects on the public and the environment.

After consideration of the above and the adverse effects of the proposed bypass and any other relevant factors, the Department will approve or deny the request. The public shall be notified and given an opportunity to comment on bypass incidents of significant duration, to the extent feasible. Approval of a request to bypass will be by administrative order issued by the Department under RCW 90.48.120.

3. Bypass for Essential Maintenance Without the Potential to Cause Violation of Permit Limits or Conditions—Bypass is authorized if it is for essential maintenance and does not have the potential to cause violations of limitations or other conditions of the permit, a violation of a pretreatment standard or requirement, or adversely impact public health as determined by the Department prior to the bypass.

C. Best Management Practices\Pollution Prevention Program

1. Chemical Storage

Solid chemicals, chemical solutions, paints, oils, solvents, acids, caustic solutions, and waste materials, including used batteries, shall be stored in a manner which will prevent the inadvertent entry of these materials into waters of the state, including ground waters, and in a manner that will prevent spillage by overfilling, tipping, or rupture. In addition, the following practices shall be used.

- a. All liquid products shall be stored on durable impervious surface and behind berms.
- b. Chemicals shall be stored and dispensed only in roofed and bermed areas to eliminate potential spills to waters of the state or contamination of stormwater runoff.
- c. Any tank containing chemical solutions shall be located in a diked or no-outlet area that will prevent chemical loss to waters of the state or the sanitary sewer.
- d. The Permittee must contain all quenching, hydraulic, machining, and lubricating oils to prevent spills, or loss to waters of the state.
- e. Waste liquids shall be stored under cover, such as tarpaulins or roofed structures, or in a closed vessel.
- f. Incompatible or reactive materials shall be segregated and securely stored in separate containment areas that prevent the mixing of chemicals.
- g. Concentrated waste or spilled chemicals shall be disposed of at a facility approved by the Department of Ecology or appropriate county health department in accordance with the Solid Waste Disposal Plan requirements of this permit. These materials shall not be discharged to any sewer or state water.

2. Sludges and scale from the dip tanks shall be disposed of in an approved manner other than to the sewer system and other than to a state watercourse.

3. Discharge of concentrated organic solvents to the sewer system is prohibited.
4. In the event that a spill should occur within the process area, any spill control valves shall be closed to prevent the entry of concentrated chemicals to the sanitary sewers.
5. All industrial wastes containing pollutants must be treated using all known available and reasonable methods for treatment prior to discharge to the sanitary sewer.

S5. PROHIBITED DISCHARGES

A. General Prohibitions

The Permittee shall not introduce into the POTW pollutant(s) which cause pass through or interference.

B. Specific Prohibitions

In addition, the following shall not be introduced into the POTW:

1. Pollutants which create a fire or explosion hazard in the POTW, including, but not limited to, waste streams with a closed cup flashpoint of less than 60° C (140° F) using the test methods specified in 40 CFR 261.21;
2. Solid or viscous pollutants in amounts which will cause obstruction to the flow in the POTW resulting in interference;
3. Any pollutant, including oxygen-demanding pollutants (BOD, etc.), released in a discharge at a flow rate and/or pollutant concentration which will cause interference with the POTW;
4. Heat in amounts which will inhibit biological activity in the POTW resulting in interference, but in no case heat in such quantities that the temperature at the POTW treatment plant exceeds 40° C (104° F) unless the approval authority, upon request of the POTW, approves alternative temperature limits;
5. Petroleum oil, non-biodegradable cutting oil, or products of mineral oil origin in amounts that will cause interference or pass through;
6. Pollutants which result in the presence of toxic gases, vapors, or fumes within the POTW in a quantity that may cause acute worker health and safety problems;
7. Any trucked or hauled pollutants, except at discharge points designated by the POTW.

C. Prohibited Unless Approved

1. Any of the following discharges are prohibited unless approved by the Department under extraordinary circumstances (such as a lack of direct discharge alternatives due to combined sewer service or a need to augment sewage flows due to septic conditions):
 - a. Non-contact cooling water in significant volumes.
 - b. Storm water and other direct inflow sources.
 - c. Wastewaters significantly affecting system hydraulic loading, which do not require treatment or would not be afforded a significant degree of treatment by the system.
2. Unless specifically authorized in this permit, the discharge of dangerous wastes as defined in Chapter 173-303 WAC, is prohibited.

S6. DILUTION PROHIBITED

The Permittee shall not dilute the wastewater discharge with stormwater or increase the use of potable water, process water, non-contact cooling water, or, in any way, attempt to dilute an effluent as a partial or complete substitute for adequate treatment to achieve compliance with the limitations contained in this permit.

S7. SOLID WASTE DISPOSAL**A. Solid Waste Handling**

The Permittee shall handle and dispose of all solid waste material in such a manner as to prevent its entry into state ground water, surface water, or a POTW.

B. Leachate

The Permittee shall not allow leachate from its solid waste material to enter state waters without providing all known, available, and reasonable methods of treatment, nor allow such leachate to cause violations of the State Surface Water Quality Standards, Chapter 173-201A WAC, or the State Ground Water Quality Standards, Chapter 173-200 WAC. The Permittee shall apply for a permit or permit modification as may be required for such discharges to state ground or surface waters.

C. Solid Waste Control Plan

The Permittee shall maintain a solid waste control plan for the facility covered by this permit. This plan shall include all solid wastes with the exception of those solid wastes regulated by Chapter 173-303 WAC (Dangerous Waste Regulations). The plan shall include at a minimum a description, source, generation rate, and disposal methods of these solid wastes. This plan shall not be at variance with any approved local solid waste management plan.

The Permittee shall comply with the plan and any modifications thereof. The Permittee shall submit significant modification of the solid waste plan to the Department within thirty (30) days of their adoption.

S8. NON-ROUTINE AND UNANTICIPATED DISCHARGES

Beginning on the effective date of this permit, the Permittee may discharge non-routine wastewater on a case-by-case basis if approved by the Department. Prior to any such discharge, the Permittee shall contact the Department and **at a minimum** provide the following information:

1. The nature of the activity that is generating the discharge.
2. Any alternatives to the discharge, such as reuse, storage, or recycling of the water.
3. The total volume of water expected to be discharged.
4. The results of the chemical analysis of the water. All discharges must comply with the effluent limitations as established in Special Condition S1. of this permit, water quality standards, sediment management standards, and any other limitations imposed by the Department.
5. The date of proposed discharge and the rate at which the water will be discharged, in gallons per minute. The discharge rate shall be limited to that which will not cause erosion of ditches or structural damage to culverts and their entrances or exits.
6. If the proposed discharge is to a municipal storm drain and is approved by the Department, the Permittee shall notify the municipality of the discharge.

The discharge cannot proceed until the Department has reviewed the information provided and has authorized the discharge. Authorization from the Department will be by letter to the Permittee or by an Administrative Order.

S9. SPILL PLAN

The Permittee shall maintain a Spill Control Plan for the prevention, containment, and control of spills or unplanned releases. The Permittee shall review the plan at least annually and update the Spill Plan as needed. Changes to the plan shall be sent to the Department within thirty (30) days of their adoption. The plan and any supplements shall be followed throughout the term of the permit.

The updated Spill Control Plan shall include the following:

- A description of operator training to implement the plan;
- A description of the reporting system which will be used to alert responsible managers and legal authorities in the event of a spill;
- A description of preventive measures and facilities (including an overall facility plot showing drainage patterns) which prevent, contain, or treat spills of these materials; and,

- A list of all oil and petroleum products, materials, which when spilled, or otherwise released into the environment, are designated Dangerous Waste (DW) or Extremely Hazardous Waste (EHW) by the procedures set forth in WAC 173-303-070, or other materials which may become pollutants or cause pollution upon reaching state's waters.

Plans and manuals required by 40 CFR Part 112, contingency plans required by Chapter 173-303 WAC, or other plans required by other agencies which meet the intent of this section may be submitted.

S10. SLUG DISCHARGE CONTROL PLAN

The Permittee shall maintain a plan to minimize the potential of slug discharges to the POTW from the facility covered by this permit. Such plan shall include the following information and procedures relating to the prevention of unauthorized slug discharges:

1. A description of a reporting system to be used to immediately notify facility management, the POTW operator, and appropriate state, federal, and local authorities of any slug discharges, and provisions to provide a written follow-up report within five days;
2. A description of operator training, equipment, and facilities (including overall facility plan) for preventing, containing, or treating slug discharges;
3. A list of all raw materials, products, chemicals, and hazardous materials used, processed, or stored at the facility; the normal quantity maintained on the premises for each listed material; and a map showing where they are located.
4. A description of discharge practices for batch and continuous processes under normal and non-routine circumstances;
5. A brief description of any unauthorized discharges which occurred during the 36-month period preceding the effective date of this permit and subsequent measures taken by Permittee to prevent or to reduce the possibility of further unauthorized discharges; and
6. An implementation schedule including additional operator training and procurement and installation of equipment or facilities required to properly implement the plan.

The Permittee shall review its slug discharge plan periodically, and update it as needed but not less than once each two years. All revisions or updates of this plan shall be submitted to the Department within thirty days of their adoption. The current approved plan shall be maintained on the plant site and be readily available to facility personnel. The Permittee shall submit an update of the slug discharge control plan, or a certification that it is current with the application for permit renewal.

S11. TOXIC ORGANIC MANAGEMENT PLAN

The Permittee shall maintain, and implement, an adequate Toxic Organic Management Plan. The Permittee shall periodically review the plan for adequacy, and update it as necessary. The Permittee is required to submit any modifications to the plan to the Department no later than thirty days following adoption of such modifications. Toxic organic compounds for the purposes of this plan shall include not only those compounds listed under 40CFR Part 433.11, but also any other organic compounds such as ketones, aromatics, or halogenated hydrocarbon compounds, which, when present in aqueous solutions at concentrations of greater than ten percent by weight, are toxic to aquatic life. The Permittee may submit the toxic organic management plan as part of the spill prevention plan.

The Toxic Organic Management Plan shall, at a minimum contain the following items:

- 1) A description of storage and handling measures to be employed prevent or minimize entry of toxic organic compounds into the environment
- 2) A description of measures to be employed for minimization of use of toxic organic compounds. Such measures may include, but are not limited to distillation and re-use, recycling, substitution by alkaline cleaning operations, substitution by less toxic compounds.
- 3) Plans for training employees regarding the contents of the Toxic Organic Management Plan.

S12. STORMWATER POLLUTION CONTROL

1. This permit does not authorize discharge of process wastewater, such as metal finishing rinse water, to surface waters or storm sewers. This permit also does not authorize the discharge of compressor blowdown to the stormsewer.
2. The Permittee shall maintain a Stormwater Pollution Prevention Control Plan. The plan shall include the following items at a minimum:
 - a. A good housekeeping plan to prevent discharge of process or polluted non-process wastewater to surface waters.
 - b. A preventative maintenance program for the inspection and maintenance of stormwater management devices and other equipment at the facility, and follow-up procedures to ensure continued implementation.
 - c. Description of spill cleanup procedures, equipment, and personnel.
 - d. A training plan for training employees annually on your stormwater prevention plan requirements.
 - e. A description of practices designed to control pollution at its sources.

- f. Procedures and schedule for inspecting stormwater drainage areas for evidence of pollutants entering the drainage systems.
- g. Procedures and schedule for performing maintenance checks of structural measures to ensure that they are operating properly.

GENERAL CONDITIONS

G1. SIGNATORY REQUIREMENTS

All applications, reports, or information submitted to the Department shall be signed as follows:

- A. All permit applications shall be signed by either a principal executive officer or ranking elected official.
- B. All reports required by this permit and other information requested by the Department shall be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:
 - 1. The authorization is made in writing by the person described above and is submitted to the Department at the time of authorization, and
 - 2. The authorization specifies either a named individual or any individual occupying a named position.
- C. Changes to authorization. If an authorization under paragraph B.2. above is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization must be submitted to the Department prior to or together with any reports, information, or applications to be signed by an authorized representative.
- D. Certification. Any person signing a document under this section shall make the following certification:

"I certify under penalty of law, that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

G2. RIGHT OF ENTRY

Representatives of the Department shall have the right to enter at all reasonable times in or upon any property, public or private, for the purpose of inspecting and investigating conditions relating to the pollution or the possible pollution of any waters of the state. Reasonable times shall include normal business hours; hours during which production, treatment, or discharge occurs; or times when the Department suspects a violation requiring immediate inspection. Representatives of the Department shall be allowed to have access to, and copy at reasonable cost, any records required to be kept under terms and conditions of the permit; to inspect any monitoring equipment or method required in the permit; and to sample the discharge, waste treatment processes, or internal waste streams.

Officials of the City of Marysville Public Works Department shall have the same right of entry as that granted to the Department for purposes of assessing compliance with this permit.

G3. PERMIT ACTIONS

This permit shall be subject to modification, suspension, or termination, in whole or in part by the Department for any of the following causes:

- A. Violation of any permit term or condition;
- B. Obtaining a permit by misrepresentation or failure to disclose all relevant facts;
- C. A material change in quantity or type of waste disposal;
- D. A material change in the condition of the waters of the state; or
- E. Nonpayment of fees assessed pursuant to RCW 90.48.465.

The Department may also modify this permit, including the schedule of compliance or other conditions, if it determines good and valid cause exists, including promulgation or revisions of regulations or new information.

G4. REPORTING A CAUSE FOR MODIFICATION

The Permittee shall submit a new application, or a supplement to the previous application, along with required engineering plans and reports, whenever a new or increased discharge or change in the nature of the discharge is anticipated which is not specifically authorized by this permit. This application shall be submitted at least sixty (60) days prior to any proposed changes. Submission of this application does not relieve the Permittee of the duty to comply with the existing permit until it is modified or reissued.

G5. PLAN REVIEW REQUIRED

Prior to constructing or modifying any wastewater control facilities, an engineering report and detailed plans and specifications shall be submitted to the Department for approval in accordance with Chapter 173-240 WAC. Engineering reports, plans, and specifications should be submitted at least one hundred eighty (180) days prior to the planned start of construction. Facilities shall be constructed and operated in accordance with the approved plans.

G6. COMPLIANCE WITH OTHER LAWS AND STATUTES

Nothing in the permit shall be construed as excusing the Permittee from compliance with any applicable federal, state, or local statutes, ordinances, or regulations.

G7. DUTY TO REAPPLY

The Permittee must apply for permit renewal at least one hundred eighty (180) days prior to the specified expiration date of this permit.

G8. PERMIT TRANSFER

This permit is automatically transferred to a new owner or operator if:

- A. A written agreement between the old and new owner or operator containing a specific date for transfer of permit responsibility, coverage, and liability is submitted to the Department;
- B. A copy of the permit is provided to the new owner and the receiving POTW is notified; and
- C. The Department does not notify the Permittee of the need to modify the permit.

Unless this permit is automatically transferred according to section A. above, this permit may be transferred only if it is modified to identify the new Permittee and to incorporate such other requirements as determined necessary by the Department.

G9. REDUCED PRODUCTION FOR COMPLIANCE

The Permittee shall control production or discharge to the extent necessary to maintain compliance with the terms and conditions of this permit upon reduction of efficiency, loss, or failure of its treatment facility until the treatment capacity is restored or an alternative method of treatment is provided. This requirement applies in the situation where, among other things, the primary source of power for the treatment facility is reduced, lost, or fails.

G10. REMOVED SUBSTANCES

Collected screenings, grit, solids, sludges, filter backwash, or other pollutants removed in the course of treatment or control of wastewaters shall not be resuspended or reintroduced to the effluent stream for discharge.

G11. PAYMENT OF FEES

The Permittee shall submit payment of fees associated with this permit as assessed by the Department. The Department may revoke this permit if the permit fees established under Chapter 173-224 WAC are not paid.

G12. PENALTIES FOR VIOLATING PERMIT CONDITIONS

Any person who is found guilty of willfully violating the terms and conditions of this permit shall be deemed guilty of a crime, and upon conviction thereof shall be punished by a fine of up to ten thousand dollars and costs of prosecution, or by imprisonment in the discretion of the court. Each day upon which a willful violation occurs may be deemed a separate and additional violation.

Any person who violates the terms and conditions of a waste discharge permit shall incur, in addition to any other penalty as provided by law, a civil penalty in the amount of up to ten thousand dollars for every such violation. Each and every such violation shall be a separate and distinct offense, and in case of a continuing violation, every day's continuance shall be and be deemed to be a separate and distinct violation.